

wineo-insulation board


Sound Protect Eco Profi | Technical characteristics

Description

The patented acoustic system, "Sound Protect Eco Profi" has been specially designed for floating installation under laminate, engineered wood and other hard wood flooring. The high quality "Sound Protect Eco Profi" footfall and impact noise system is made of up to 90 % natural raw materials and is supplied conveniently on a roll.

Product composition:

Resilient underlay material consisting of mineral fillers and polyurethane binding agents. The "Sound Protect Eco Profi" system consists of a PET carrier film, an ageing resistant heavy layer of polyurethane and a high quality nonwoven backing (in white).



Technical details

Dimensions:

Thickness	2.80 mm (± 0.15 mm)
Weight/m ²	2.80 kg/m ² (± 0.15 kg/m ²)
Roll	5.00 x 1.00 m = 5 m ² (length ± 10.00 mm / width ± 1.00 mm)
Weight/roll	approx. 15 kg/roll

Package / Form of delivery:

Pallet	40 rolls = approx. 200 m ² Rolls on tube in wrap foil, with installation instruction
--------	--

Underfloor heating	Ideal for use on warm water underfloor heating
--------------------	--

Thermal resistance (EN 12664)	0.01 m ² K/W
-------------------------------	-------------------------

Footfall noise reduction (DIN EN 10140)	> 20 dB
---	---------

Room Sound reduction (EPLF-standard 021029-5)	approx. 31 %
---	--------------

Reaction to fire (DIN 13501-1)	E _{fl}
--------------------------------	-----------------

Pressure stability (250 Pa, 0.5 mm) (acc. to DIN EN 826)	up to 15 t/m ² (~ 150 kPa)
--	---------------------------------------

S _D value (DIN EN 12086)	< 75 m
-------------------------------------	--------

Characteristics / Information

Fields of application	Room sound reduction and footfall noise reduction under hard floors. Suitable especially for click-systems.
-----------------------	---

Fields of use	New development and modernization
---------------	-----------------------------------

Environment / Disposal

Responsibility / Compatibility	wineo Sound Protect Eco Profi is FREE of plasticisers, asbestos, formaldehyde, halogens and heavy metals and meets the VOC guidelines for classifications A+, Blue Angel and the AgBB scheme.
--------------------------------	---

Ecology	Production is done without using substances that damage the ozone layer. The mat is free of solvents. The renewable raw materials used for the product do not compete with food crops.
---------	---

Occupational safety and environmental protection	The product does not require any special occupational safety measures. When installing the floor coverings, it is <u>essential</u> to comply with the manufacturer's protection specifications.
--	---

Waste disposal	Landfill and waste incineration site
----------------	--------------------------------------

Waste disposal code	No. 170604
---------------------	------------

Installation

Sound Protect Eco Profi is installed at right angles to the installation direction of the surface covering and cut to size. Easy and dust-free cutting with a universal or cutter knife. Install with the nonwoven site facing down and the film side facing up towards the surface covering. Adjoining edges must be laid close together. Stick down the edges of the mats with combination sealing tape. Only suitable for floating installation.

Note:

The information above is based on the current state of knowledge and technical development. We make no claim as to the completeness of the information. Windmüller flooring products GmbH reserves the right to make technical changes.